



SPECIFICATIONS	
Air Flow:	> 50 l/s
Diameter:	150dia
Duct Run:	Back to back install
Noise:	58dB (low power)
Install Location:	Kitchen
Minimum Clearance:	NA
Rooms Served:	One
Ventilation Type:	Kitchen extract
Filter:	Grease filter
Control:	3 Speed push button
Power:	102W
Add-ons:	NA

## PRODUCT DESCRIPTION

Rangehood installed "back-to-back", going through wall immediately behind rangehood.

## **KEY BENEFITS**

 Simple and effective: The most straight forward path is often the best one. Back-to-back installations allow for extra short duct runs with no fuss and easy install.

### **APPLICATIONS**

\*This system is suitable for, but not limited to the following areas:

Kitchen extract direct through exterior wall, any level.

## PRODUCT COMPLIANCE

- G4: Extract air volume exceeds 50l/s for kitchens
- Healthy Homes: Kitchen Ventilation
- B2, E2

#### **ELECTRICAL**

- Electrical connection excluded.
- All fans to be connected to an isolating switch as per AS/NZS 3000:2018.

#### **WARRANTY**

- 2 Year rangehood warranty
- 10 Years for materials and workmanship

Terms and conditions apply.

## **EXPANSIONS / ALTERNATIVES**

- HTKKBH: For bulkhead / short ducted installations
- HTKKDU: For longer duct runs
- HTKKTR: For through roof installations
- HTPOTW: When supplying your own range hood
- HTKKTW: For fire rated exterior wall applications

## **LIMITATIONS**

- Must be installed on an external wall.
- Sufficient replacement air is required for extract efficiency.
- Rangehood fire requirements should be co-ordinated with the fire engineer at design stage.

# INSTALLATION

To be carried out by Hometech to manufacturer's recommendations:

- Rangehoods to be hung after painting and cabinetry install.
- Power point should be supplied by others.

#### **MAINTENANCE**

- Grease filters should be cleaner regularly with warm soapy water or in the dishwasher.
- Rangehood exterior surfaces can be cleaned with a damp cloth.
- If any problems arise, please contact your installation professional.

