

HTPOTR

PENETRATION SERIES THROUGH ROOF
COMPATIBLE WITH FAN / RANGEHOOD



hometechTM
The Ventilation Specialists



SPECIFICATIONS

Air Flow:	NA
Diameter:	150dia
Duct Run:	3m
Install Location:	Bathroom / Kitchen Connections
Minimum Clearance:	350mm
Rooms Served:	One
Ventilation Type:	Extraction
Filter:	NA
Control:	NA
Add-ons:	Rangehood Installation: If you wish to supply your own rangehood for installation, Hometech can undertake the installation of supplied rangehood as an optional extra for single room options.

PRODUCT DESCRIPTION

The Hometech proprietary roof penetration with cap and ducting. Installed as a "penetration only", ducting is left loose for connection to rangehood or fans installed by others.

KEY BENEFITS

- Simple: Using Hometechs proprietary flashing and vent cap it's takes what we already and applies it to a common problem.
- Smart Installation: Roof penetrations often offer the path of least resistance for ducting, which in turn leads to more efficient performance from fans
- Optional 2-in-1: One penetration can serve multiple spaces, minimising exterior penetrations
- Peace of mind: backed up by a 10-year leak proof guarantee

APPLICATIONS

*This system is suitable for, but not limited to the following areas:

- Penetration for applications where an alternative fan to the standard Hometech option needs to be used. Compatible with rangehoods and bathroom fans.

PRODUCT COMPLIANCE

- B2, E2
- BRANZ appraisal 665

WARRANTY

- 10 Year LEAK PROOF GUARANTEE
- 10 Years for materials and workmanship

Terms and conditions apply.

EXPANSIONS / ALTERNATIVES

- HTPOTR2R : Two room variation
- HTPVTR: Passive vent option with ducting and ceiling grille (no fan)
- HTPVTRAG: Through roof penetration with no ducting (passive)
- HTPOTW: Through wall option
- HTPOBH: Through wall option with ducting

LIMITATIONS

- Penetration only systems are designed to allow you to work with Hometech's 10-year leak proof guarantee for your penetrations, while still using specific fans installed by others, or installed as a separable part of the contract by Hometech.
- The two room option connects both ducts at the roof level not through a jointer to prevent the chance of back drafting between runs.

INSTALLATION

To be carried out by Hometech to manufacturer's recommendations:

- Roof mounted system installed with proprietary Hometech roof flashing (BRANZ Appraisal 665).
- Roof work to be carried out safely, where possible use of scaffolding or mobile work platforms recommended.
- Allow roof access for future maintenance.

MAINTENANCE

- As there are no operable parts no maintenance is required.
- Fan's installed by others will have their own requirements.

CAD DRAWING

Full CAD drawing(s) available upon request

