



## PRODUCT DESCRIPTION

Rangehood installed with 150dia ducting through roof, up to 3m.

## KEY BENEFITS

- Efficient operation: Roof penetrations often offer the path of least resistance for ducting which in turn leads to quieter, more efficient performance from fans.
- Peace of mind: backed up by a 10-year leak proof guarantee.
- Reduce cooking smells: With an exhaust point mounted on your roof it's further from windows and habitable spaces.

## APPLICATIONS

\*This system is suitable for, but not limited to the following areas:

- Kitchen extract exhausted through roof, primarily single storey vertical exhaust.
- Options available for multistorey vertical exhaust.

## PRODUCT COMPLIANCE

- G4: Extract air volume exceeds 50l/s for kitchens
- Healthy Homes: Kitchen Ventilation
- B2, E2
- BRANZ appraisal 665

## ELECTRICAL

- Electrical connection excluded.
- All fans to be connected to an isolating switch as per AS/NZS 3000:2018.

## WARRANTY

- 10 Year LEAK PROOF GUARANTEE
- 2 Year rangehood warranty
- 10 Years for materials and workmanship

Terms and conditions apply.

## SPECIFICATIONS

Air Flow:	>50 l/s
Diameter:	150dia
Duct Run:	Up to 3m
Noise:	58dB (low power)
Install Location:	Kitchen
Minimum Clearance:	Suitable for skillion ceilings
Rooms Served:	One
Ventilation Type:	Kitchen extract
Filter:	Grease filter
Control:	3 Speed push button
Power:	102W
Add-ons:	NA

## EXPANSIONS / ALTERNATIVES

- HTKKTW : For back to back installs
- HTKKBH : For bulkhead / short ducted installations
- HTKKDU : For longer duct runs
- HTPOTR : When supplying your own range hood

## LIMITATIONS

- Sufficient replacement air is required for extract efficiency.
- Rangehood fire requirements should be co-ordinated with the fire engineer at design stage.

## INSTALLATION

To be carried out by Hometech to manufacturer's recommendations:

- Rangehoods to be hung after painting and cabinetry install.
- Power point should be supplied by others.

## MAINTENANCE

- Grease filters should be cleaned regularly with warm soapy water or in the dishwasher.
- Rangehood exterior surfaces can be cleaned with a damp cloth.
- If any problems arise, please contact your installation professional.

## CAD DRAWING

Full CAD drawing(s) available upon request

